

# DECLARATION OF PERFORMANCES

WPBSP339

1. Number and/or identification code:

**WPBSP339**

2. Name, type, batch or serial number:

**MOPLY N PLUS 2,5 KG AL NATURAL**

3. Intended uses:

**Flexible bitumen sheets for water vapour control layers.**

4. Name and contact adress of the manufacturer:

**TEXSA SYSTEMS SLU - C/ Ferro, 7 - Pol. Can Pelegrí - 08755 Castellbisbal - Barcelona (SPAIN)**

5. System or systems of assessment and verification of constancy of performance:

**System 3**

6. Name and identification number of the notified body and tasks:

Task carried out:

System

Done / Issued:

**Fire reaction**

**3**

**APPLUS-LGAI**

7. Declared performance


Essential characteristics	Performance	Harmonised technical specification
Fire reaction	E	EN 13970:2004
Watertightness after stretching at low temperature	Pass	
Water vapour transmission properties (kg/m <sup>2</sup> ·s)	≤ 2·10E-8	
Tensile properties:		
Maximum tensile strength (L x T) (N/50mm)	280 ± 100    280 ± 100	
Elongation (L x T) (%)	NPD	
Impact resistance (mm)	NPD	
Joint shear resistance (L x T) (N/50mm)	NE	
Flexibility at low temperature (°C)	≤ -10	
Tear strength (nail) (L x T) (N)	NE	
Durability (Vapour resist. / Chemical resist.)	Pass / NE	
Hazardous substances	NPD	

NE - Not relevant, NPD - No performance determined

The performance of the product identified in points 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:



J. Fiter  
RD& i Director

Castellbisbal, 19/10/2015

