



# DECLARATION OF PERFORMANCES

WPBSP129

1. Number and/or identification code:

**WPBSP129**

2. Name, type, batch or serial number:

**MORTERPLAS FP 4 KG**

LBM-40-FP

3. Intended uses:

**Reinforced bitumen sheets for roof waterproofing. Bitumen basement tanking sheets (Type T)**

4. Name and contact address of the manufacturer:

**TEXSA SYSTEMS SLU - C/ Ferro, 7 - Pol. Can Pelegrí - 08755 Castellbisbal - Barcelona (SPAIN)**

5. System or systems of assessment and verification of constancy of performance:

**System 2+**

6. Name and identification number of the notified body and tasks:

Task carried out:	System	Done / Issued:
<b>Factory Production Control (FPC)</b>	<b>2+</b>	<b>AENOR - 0099</b>
		on the basis of: <b>0099/CPR/A85/0087</b>
<b>Fire reaction</b>	<b>3</b>	<b>APPLUS-LGAI</b>
<b>External fire behaviour</b>	<b>3</b>	<b>APPLUS-LGAI</b>

7. Declared performance


Essential characteristics	Performance	Harmonised technical specification
<b>Watertightness</b>	<b>Pass (60 kPa)</b>	<b>EN 13707:2005+A2:2010</b> <b>EN 13969:2004</b>
<b>Tensile properties:</b>		
<b>Maximum tensile strength (L x T) (N/50mm)</b>	<b>700 ± 200    450 ± 150</b>	
<b>Elongation (L x T) (%)</b>	<b>45 ± 15    45 ± 15</b>	
<b>Tear strength (nail) (L x T) (N)</b>	<b>180 x 220 ± 50</b>	
<b>Flexibility at low temperature (°C)</b>	<b>≤ -15</b>	
<b>Durability (flexibility / flow resistance)</b>	<b>NPD</b>	
<b>External fire behaviour</b>	<b>Broof(t1)</b>	<b>EN 13707:2005+A2:2010</b>
<b>Fire reaction</b>	<b>E</b>	
<b>Root penetration resistance</b>	<b>NPD</b>	
<b>Static load resistance (kg)</b>	<b>≥ 15</b>	
<b>Impact resistance (mm)</b>	<b>≥ 1000</b>	
<b>Durability (Watertightness)</b>	<b>Pass (60 kPa)</b>	<b>EN 13969:2004</b>
<b>Watertightness durability against chemical agents</b>	<b>NPD</b>	
<b>Hazardous substances</b>	<b>NPD</b>	

NE - Not relevant, NPD - No performance determined

The performance of the product identified in points 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, consisting of a circular scribble with vertical lines inside, and a long horizontal stroke extending to the left.

**J. Fiter**  
**RD& i Director**

**Castellbisbal, 29/05/2015**

---